

Typ: Neozed D01 - D03

440V AC
od 2 do 100A

Wg norm: D EN 60269-1 i 4

| Rozmiar | Prąd | Napięcie | Numer referencyjny | Opakowanie |
|---------|------|----------|--------------------|------------|
| | A | V AC | | |
| D01 | 2 | 440V | M215038P | 50 |
| D01 | 4 | 440V | N218673P | 50 |
| D01 | 6 | 440V | B219191P | 50 |
| D01 | 10 | 440V | F219724P | 50 |
| D01 | 16 | 440V | N222169P | 50 |
| D02 | 20 | 440V | H222923Y | 30 |
| D02 | 25 | 440V | R200713Y | 30 |
| D02 | 35 | 440V | F201255Y | 30 |
| D02 | 50 | 440V | R201771Y | 30 |
| D02 | 63 | 440V | Y207113Y | 30 |
| D03 | 80 | 440V | G211514J | 10 |
| D03 | 100 | 440V | L212024J | 10 |



| Rozmiar | Prąd | Przedłukowe J ² t | J ² t | Strata mocy | kg / 100 szt. |
|---------|------|------------------------------|------------------|-------------|---------------|
| | A | A ² s | A ² s | W | |
| D01 | 2 | 3 | 3 | 1,5 | 0,62 |
| | 4 | 4 | 5 | 2,0 | 0,62 |
| | 6 | 5 | 10 | 2,3 | 0,62 |
| | 10 | 12 | 25 | 2,2 | 0,62 |
| | 16 | 40 | 75 | 3,3 | 0,62 |
| D02 | 20 | 60 | 110 | 4,3 | 1,40 |
| | 25 | 90 | 180 | 6,0 | 1,40 |
| | 35 | 210 | 410 | 8,4 | 1,40 |
| | 50 | 830 | 1650 | 10,0 | 1,40 |
| | 63 | 1300 | 2500 | 13,9 | 1,40 |
| D03 | 80 | 2100 | 4300 | 17,6 | 3,70 |
| | 100 | 3300 | 6600 | 21,0 | 4,10 |

Charakterystyki czasowo - prądowe

